

County Surveyor's Record, Douglas County, Oregon

NO PAGE # 17178

Dependent Resurvey, Portion of the Subdivisional Lines, **17978**
T. 29 S. R. 7 W., Willamette Meridian, Oregon

CHAINS

T 29 S	R 7 W
S 11	S 12
S 14	S 13

1957

from which bearing trees mkd. by Thielsen

A fir, 16 ins. diam., bears N. 51° E.,
200 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 44° E.,
110 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 15° W.,
70 lks. dist., with healed blaze.
(Record 74 lks.)

A fir, 19 ins. diam., bears N. 66½° W.,
61 lks. dist., with healed blaze.

S. 89° 38' W., bet. secs. 11 and 14, marking and
blazing the true line.

Ascend over NE. slope, through heavy timber and dense
undergrowth.

0.15 Spur, slopes N. 20° E.; desc. over NW. slope.

9.55 Ravine, drains N.; asc. over NE. slope.

18.05 Spur, slopes N.; desc. over NW. slope.

34.30 Creek, 3 lks. wide, course N. 40° W.; asc. over
NE. slope.

39.00 Spur, slopes N. 15° W.; desc. over NW. slope.

42.99 The 1/4 sec. cor. of secs. 11 and 14, monumented with an
iron post, 1 in. diam., firmly set, projecting 12 ins.
above ground, with brass cap mkd.

T 29 S	R 7 W
¼ S 11	
S 14	

1957

from which the remains of a bearing tree mkd. by
Thielsen

A root hole, bears South, 70 lks. dist., with
down fir alongside, 16 ins. diam., with healed
blaze.

and new bearing trees

A grand fir, 14 ins. diam., bears S. 42° W.,
68 lks. dist., mkd. 1/4 S14 BT.

A fir, 4 ins. diam., bears N. 32° W., 26 1/2 lks.
dist., mkd. X BT.

Corner is located in the edge of a clear-cut, edge
bears E. and W., timber to north.