

County Surveyor's Record, Douglas County, Oregon

17980

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

S. 89° 40' W., beginning new measurement.

Descend over NW. slope.

0.80

McNabb Creek, 5 lks. wide, course N.; asc over E. slope.

15.85

Spur, slopes N. 20° E.; desc. over NW. slope.

28.25

Creek, 1 lk. wide, course N. 20° E.; asc. over NE. slope.

34.45

Gravelled road, 20 lks. wide, bears N. 15° W. and S. 15° E.

37.10

Ridge, bears N. 5° E. and S. 5° W.; desc. NW. slope.

40.25

Gravelled road, 25 lks. wide, bears N. 35° E. and S. 35° W.

42.99

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 29 S	R 7 W
S 10	S 11
S 15	S 14

1957

from which the remains of bearing trees mkd. by Thielsen

A fir snag, 16 ins. diam., bears N. 74° E.,
39 lks. dist., with healed blaze.
(Record, N. 77½° E., 44 lks.)

A sawed fir stump, 12 ins. diam., bears
S. 70 1/2° E., 26 lks. dist., with healed blaze.
(Record, 30 lks.)

A sawed fir stump, 14 ins. diam., bears
N. 65° W., 41 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Clifford M. Bryden, Registered Engineer, No. 3937, during an unrecorded survey, in 1956.

A fir snag, 24 ins. diam., bears N. 36° E.,
30 lks. dist., with healed double blaze.

A sawed fir stump, 24 ins. diam., bears
S. 19 1/2° E., 12 1/2 lks. dist., with healed
double blaze.

A fir, 17 ins. diam., bears S. 76° W.,
15 1/2 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 11 ins. diam., bears S. 31 1/2° E.,
22 lks. dist., mkd. T29S R7W S14 BT.

No other suitable trees available.

Corner is located in the SE. cor. of a logged area, edge bears N. and W.