

County Surveyor's Record, Douglas County, Oregon

17982

Subdivision of Section 11,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

78.09

The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 29 S R 7 W
 $\frac{1}{4}$ $\frac{S 2}{S 11}$

1957

from which bearing trees mkd. by H. L. Eppstein, Deputy County Surveyor, in 1923

A fir, 25 ins. diam., bears S. 57 1/2° E.,
33 lks. dist., with healed double blaze.

A fir, 32 ins. diam., bears S. 72° W.,
26 lks. dist., with fragmentary scribe
marks visible on opened blaze.

and a bearing tree mkd. by Thielsen

A fir, 20 ins. diam., bears N. 32° W.,
61 lks. dist., with healed blaze.

From this point, United States Coast and Geodetic Survey triangulation station TWO OAKS 1942", bears N. 69° 02' E., 87.29 chs. dist., monumented with an iron post 2 ins. diam., firmly set, projecting 6 ins. above ground, with a standard brass cap, 3 1/2 ins. diam., mkd. TWO OAKS 1942, and a triangle.

From the 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 29 S R 7 W
 $\frac{1}{4}$
 S 11 | S 12
 1957

from which bearing trees mkd. by Thielsen

A fir, 16 ins. diam., bears N. 54° E.,
46 lks. dist., with healed blaze.
(Record, N. 43° E., 40 lks.)

A madrone, 42 ins. diam., bears S. 1° W.,
67 lks. dist., with fragmentary scribe
marks visible on partially healed blaze.
(Record, S. 6° W.)

S. 88° 54' W., on the E. and W. center line of sec. 11.

Descend over SW. slope, through heavy timber and dense undergrowth.

3.00

Ravine, drains. S. 15° E.; asc. over SE. slope.

18.10

Ridge, bears N. 10° E. and S. 10° W.; desc. over broken SW. slope

42.90

The center 1/4 sec. cor. of sec. 11.

Descend along creek bottom.