

# County Surveyor's Record, Douglas County, Oregon

17987

Dependent Resurvey, Portion of the Subdivisional Lines  
T. 28 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

COUNTY SURVEYORS OFFICE

T 28 S    R 4 W

S 6 | S 5

S 7 | S 8

1959

from which the remaining original bearing tree

A madrone, 40 ins. diam., bears S. 40° W.,  
40 lks. dist. with fragmentary scribe  
marks visible on partially healed blaze.

and bearing trees mkd. by Byron

A fir, 59 ins. diam., bears N. 67½° E.,  
81 lks. dist., with healed blaze.  
(Record, 77 lks.)

A fir, 25 ins. diam., bears S. 7° E.,  
21½ lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 16° W.,  
24 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 8° W.,  
34 lks. dist., with healed blaze.

N. 88° 45' W., bet. sec.s 6 and 7, marking and blazing  
the true line.

Ascend over SE. slope, through heavy timber and dense  
undergrowth.

5.00      Ridge, bears N. and S.; desc. over broken NW. slope,  
changing to SW. slope, also dirt road, 15 lks. wide,  
bears N. and S.

37.05      Creek, 2 lks. wide, course N. 60° W.; asc. over NE.  
slope.

37.45      Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.

39.77      Point for the ¼ sec. cor. of secs. 6 and 7, at propor-  
tionate dist.; there is no remaining evidence of the  
original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 28 S    R 4 W

¼    S 6

      S 7

1984

from which

A fir, 9 ins. diam., bears N. 86½° E.,  
13 lks. dist., mkd. ¼ S6 BT.

A fir, 10 ins. diam., bears S. 3½° E.,  
37 lks. dist., mkd. ¼ S7 BT.

Ascend over NE. slope.

46.95      Spur, slopes N. 20° W.; desc. over W slope.