

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

17988

CHAINS

From the 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 28 S R 4 W
 $\frac{1}{4}$ $\frac{S 7}{S 18}$
 1974

from which the remaining original bearing tree

A fir, 37 ins. diam., bears N. 60° E.,
28 lks. dist., with scribe marks 7 BT CS
visible on partially healed blaze.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1961

A fir, 15 ins. diam., bears S. 42° E.,
40 lks. dist., with healed double blaze.

From this point, United States Coast and Geodetic Survey triangulation station DODSON 1942, bears S 41° 29' W., 168.33 chs. dist., monumented with a standard brass tablet, 3½ ins. diam., set in bedrock, with top mkd. DODSON 1942, and a triangle.

The corner is located at a fence corner, barbed wire fences extending N., E., and W.

N. 0° 12' E., on the N. and S. center line of sec. 7, marking and blazing the true line.

Descend over broken NW. slope, through heavy timber and dense undergrowth.

18.70 Ravine, drains N. 85° W.; asc. over SW. slope.

19.81 Point for the center S 1/16 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C
 S 1/16 | S 7
 C
 1984

from which

A cedar, 10 ins. diam., bears S. 70° E.,
175 lks. dist., mkd. CS 1/16 S7 BT.

A fir, 18 ins. diam., bears S. 18½° W.,
130 lks. dist., mkd. CS 1/16 S7 BT.

Ascend over broken SW. slope.

35.50 Powerline, 2 wire service line, bears N. 60° E. and S. 60° W.

37.05 Spur, slopes S. 65° E., to saddle; desc. over broken NE. slope.

39.62 Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line.