

# County Surveyor's Record, Douglas County, Oregon

17990

Subdivision of Section 7,  
T.28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 4 W  
C ¼  
S 7  
1984

from which

A fir, 4 ins. diam., bears N. 59° E.,  
20 lks. dist., mkd. X BT.

A fir, 9 ins. diam., bears S. 62½° W.,  
5 lks. dist., mkd. C ¼ S7 BT.

Descend over broken NE. slope, changing to NW. slope.

61.80 Dry creek bed, 5 lks. wide, course S. 55° W.; asc over SE. slope.

61.95 Powerline, 2 wire service line, bears N. 60° E. and S. 60° W.

62.25 Gravelled road, 25 lks. wide, bears N. 60° E. and S. 60° W.

73.15 Spur, slopes S. 70° E., to saddle; desc. over NE. slope.

79.25 The 1/4 sec. cor. of secs. 6 and 7.

From the 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd,

T 28 S R 4 W  
          ½  
S 7 | S 8  
1974

from which bearing trees mkd. by Popken

A fir, 19 ins. diam., bears S. 46° E.,  
60 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 19° W.,  
39 lks. dist., with healed blaze.

N. 88° 52' W., on the E. 2nd W. center line of sec. 7.

Descend over broken NW. slope, changing to SW. slope. through heavy timber and dense undergrowth.

2.40 Dirt road, 15 lks. wide, bears N. 5° W. and S. 5° E.

19.96 Point for the center E 1/16 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C — E 1/16 — C  
S 7  
1984