

County Surveyor's Record, Douglas County, Oregon

17992

Subdivision of Section 7,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

From the E 1/16 sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

E 1/16 $\frac{S\ 7}{S\ 18}$

1974

from which the remains of the bearing trees mkd. by Popken

A root hole, bears N. 27° E., 116 lks. dist., with down fir alongside, 12 ins. diam., with scribe marks E 1/16 S7 BT visible on open blaze.

A cedar, 16 ins. diam., bears S. 68° E., 74 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a new bearing tree

A cedar, 16 ins. diam., bears N. 11½° W., 158 lks. dist., mkd. E 1/16 S7 BT.

N. 0° 10' E., on the N. and S. center line of the SE 1/4 of sec. 7.

Descend over broken NW. slope, through heavy timber and dense undergrowth.

19.80

Point for the SE 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SE 1/4.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16
S 7

1984

from which

A fir, 8 ins. diam., bears N. 29° E., 50 lks. dist., mkd. SE 1/16 S7 BT.

A fir, 11 ins. diam., bears S. 35¼° W., 8½ lks. dist., mkd. SE 1/16 S7 BT.

Descend over broken NW. slope, changing to NE. slope.

38.25

Ravine, drains N. 55° W.; asc. over SW. slope.

39.60

The center E 1/16 sec. cor. of sec. 7.

From the S 1/16 sec. cor. of secs. 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

S 1/16
S 7 | S 8

1974