

# County Surveyor's Record, Douglas County, Oregon

17996 T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The geographic position of the 1/4 section corner of sections 15 and 22, as determined by a tie made to Lane County Public Works Department triangulation station "ROMAN 2 ECC 1973" is as follows:

Latitude 43° 49' 38" N. Longitude 123° 45' 25" W.

The mean magnetic declination is 19° E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 20 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the surveys by William Thiel, in 1877 and 1891, the retracements by W. F. Briggs, in 1892, and Alonzo Gesner, in 1894, the resurveys and survey by Fred Mensch, in 1921-22, the resurveys by Thomas Tillman and Joseph S. Gawron, in 1953-54, and Peter A. Peterson, in 1966-67, and the resurveys by Owen C. Chatters, II, in 1972, and Harvey E. Wofford, in 1982)

Beginning at the cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 20	S R 9	W
S 22	S 23	
S 27	S 26	
1953		

from which the remains of bearing trees mkd. by Tillman and Gawron

An alder snag, 22 ins. diam., bears N. 9° E., 37 lks. dist., with scribe marks S23 B visible on decayed blaze.

A cedar, 22 ins. diam., bears S. 47° E., 50 lks. dist., with scribe marks T20S visible on partially decayed blaze.

A cedar, 20 ins. diam., bears S. 4° W., 71 lks. dist., with fragmentary scribe marks visible on decayed blaze.

An alder, 21 ins. diam., bears N. 52° W., 59 lks. dist., with scribe marks T20S R9W BT visible on bark.

and a bearing tree mkd. by Wofford

An alder, 23 ins. diam., bears N. 67° E., 80 lks. dist., with scribe marks T20S R9W S23 BT visible on bark.

N. 0° 48' E., bet. secs. 22 and 23, marking and blazing the true line.

Ascend over SE. slope, through ehavy timber and dense undergrowth.