

County Surveyor's Record, Douglas County, Oregon

17998 Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, clay loam.
Timber, fir, cedar, hemlock, alder, and maple; under-
growth, vine maple, huckleberry, salmonberry, hazel, and
ferns.

From the cor. of secs. 33 and 34 only, on the S. bdy. of
the Tp., monumented with an iron post, 2 ins. diam.,
firmly set, projecting 8 ins. above ground, with brass
cap mkd.

T 20 S R 9 W
S 33 | S 34

T 21 S R 9 W
S 4
1953

from which the remains of the original bearing trees

A sawed hemlock stump, 25 ins. diam., bears
S. 21° E., 36 lks. dist., no marks visible.

A sawed fir stump, 72 ins. diam., bears
N. 14° W., 49 lks. dist., with healed blaze.
(Record, 46 lks.)

and the remains of a bearing tree mkd. by Tillman and
Gawron

A sawed cedar stump, 54 ins. diam., bears
N. 88½° E., 48 lks. dist., with fragmentary
scribe marks visible on open blaze.

and new bearing trees

A fir, 3 ins. diam., bears N. 67½° W., 22½ lks.
dist., mkd. X BT.

A fir, 6 ins. diam., bears N. 74½° W., 90½ lks.
dist., mkd. T20S R9W S33 BT.

N. 0° 15' W., bet. secs. 33 and 34.

Descend over NW. slope, through young timber and dense
undergrowth.

1.75 Creek, 2 lks. wide, course N. 80° W.; asc. over SW.
slope.

15.15 Spur, slopes W.; desc. over NW. slope.

17.00 Ravine, drains W.; asc. over SW. slope.

18.75 Spur, slopes S. 65° W.; desc. over NW. slope.

20.25 The S. 1/16 sec. cor. of secs. 33 and 34, established at
Proportionate distance and recorded by Les Roberts,
Registered Land Surveyor, No. 1039, in 1984, and is
accepted as the cor., monumented with an aluminum post,
2½ ins. diam., firmly set, projecting 4 ins. above
ground, with aluminum cap mkd.

T 20 S R 9 W
S 1/16 COR
S 33 ——— | ——— S 34
1984
FLS 1039