

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon 17999

**CHAINS**

from which bearing trees mkd. by Roberts

A maple, 6 ins. diam., bears N.  $17\frac{1}{2}^{\circ}$  E., 46 lks. dist., with scribe marks S 1/16 S34 BT visible on open blaze.

A sawed fir stump, 20 ins. diam., bears S.  $9\frac{1}{2}^{\circ}$  W., 108 lks. dist., with iron spike in base.

No other suitable trees available.

Corner is located in head of ravine, drains S.  $85^{\circ}$  W.

---

N.  $0^{\circ} 15'$  W., beginning new measurement.

Ascend over SW. slope, through young timber and dense undergrowth.

- 5.15 Spur, slopes N.  $55^{\circ}$  W.; desc. over broken NE. slope, enter heavy timber, edge bears N.  $55^{\circ}$  W. and S.  $55^{\circ}$  E.
- 16.35 Creek, 4 lks. wide, course S.  $75^{\circ}$  W.; asc. over SW. slope.
- 19.65 Spur, slopes S.  $75^{\circ}$  W.; desc. along W. slope.
- 20.25 The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

$\frac{1}{4}$   
S 33 | S 34  
1953

from which an original bearing tree

A cedar, 54 ins. diam., bears N.  $80\frac{1}{2}^{\circ}$  W., 105 lks. dist., with healed blaze. (Record, 100 lks.)

and the remains of bearing trees mkd. by Tillman and Gawron

A decayed hemlock stump, 12 ins. diam., bears N.  $75^{\circ}$  E., 23 lks. dist., with scribe marks S34 B visible on partially healed blaze. (Record, N.  $77\frac{1}{4}^{\circ}$  E.)

A maple, 19 ins. diam., bears N.  $73^{\circ}$  W., 22 lks. dist., with healed blaze. (Record, N.  $75\frac{3}{4}^{\circ}$  W.)

and a new bearing tree

A fir, 32 ins. diam., bears N.  $27\frac{1}{2}^{\circ}$  E., 174 lks. dist., mkd.  $\frac{1}{4}$  S34 BT.

---

N.  $0^{\circ} 11'$  E., beginning new measurement.

Descend along W. slope.

- 2.70 Creek, 1 lk. wide, course S.  $30^{\circ}$  W.; asc. over S. slope, changing to SW. slope.