

County Surveyor's Record, Douglas County, Oregon

18000pendent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- 13.40 Spur, slopes SW.; desc. along W. slope.
- 15.65 Head of ravine, drains SW.; asc. over SE. slope.
- 17.30 Ridge, bears N. 40° W. and S. 30° E.; desc. over NE. slope.
- 20.03 Point for the N 1/16 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 33 | S 34
1984

from which

A fir, 35 ins. diam., bears N. 4 3/4° E., 223 lks. dist., mkd. N 1/16 S34 BT.

A fir, 22 ins. diam., bears S. 5½° E., 80 lks. dist., mkd. X BT.

Continue descent over broken NE. slope, changing to general E. slope.

- 40.06 The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 20 S R 9 W
S 28 | S 27
S 33 | S 34
1953

from which an original bearing tree

A fir, 37 ins. diam., bears N. 17 3/4° W., 49 lks. dist., no marks visible on opened blaze.

and the remains of bearing trees mkd. by Tillman and Gawron

A fir, 14 ins. diam., bears N. 15¼° E., 30 lks. dist., with healed blaze. (Record, N. 13½° E.)

A fir, 21 ins. diam., bears S. 10° E., 3½ lks. dist., with healed blaze.

A fir snag, 12 ins. diam., bears S. 56¼° W., 39 lks. dist., with scribe marks S R9W S33 B visible on open blaze.

A fir, 13 ins. diam., bears N. 51 3/4° W., 27 lks. dist., with healed blaze.

and a new bearing tree

A fir, 20 ins. diam., bears S. 47¼° W., 37 lks. dist., mkd. T20S R9W S33 BT.

Land, mountainous.
Soil, shallow rocky clay loam.
Timber, fir, cedar, hemlock, alder, and maple; undergrowth, huckleberry, salmonberry, vine maple, salal, Oregon grape, poison oak, manzanita, ocean spray, ferns, and grasses.