

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

18001

| CHAINS | |
|--------|--|
| | S. 89° 18' W., bet. secs. 28 and 33. |
| | Ascend over E. slope, through heavy timber and dense undergrowth. |
| 3.50 | Spur ridge, bears N. and S.; desc. over NW. slope. |
| 6.75 | Head of ravine, drains N.; asc. over NE. slope. |
| 11.25 | Spur, slopes N. 25° W.; desc. over NW. slope. |
| 13.90 | Ravine, drains N. 20° W.; asc. over NE. slope. |
| 18.10 | Saddle in ridge, bears N. 15° W. and S. 45° E.; desc. over SW. slope. |
| 24.41 | Point for the E 1/16 sec. cor. of secs. 28 and 33. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | $E\ 1/16\ \frac{S\ 28}{S\ 33}$ 1984 |
| | from which |
| | A fir, 20 ins. diam., bears S. 71° E. 38 lks. dist., mkd. E 1/16 S33 BT. |
| | A fir, 14 ins. diam., bears N. 4 3/4° W., 32½ lks. dist., mkd. E 1/16 S28 BT. |
| | Continue descent over broken SW. slope. |
| 39.50 | Left bank of Smith River, bears N. 40° W. and S. 30° E., course S. 30° E.; thence across river. |
| 40.70 | Right bank of Smith River, bears N. 45° W. and S. 30° E.; asc. over NE. slope. |
| 42.49 | Smith River Road, asphalt surface, 35 lks. wide, bears N. 35° W. and S. 35° E. |
| 48.82 | The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. |
| | $\frac{1}{4}\ \frac{S\ 28}{S\ 33}$ 1953 |
| | from which an original bearing tree |
| | An alder, 32 ins. diam., bears N. 73½° E., 11 lks. dist., with X and ¼ chopped in bark. |
| | and bearing trees mkd. by Tillman and Gawron |
| | A fir, 55 ins. diam., bears S. 13¼° E., 55 lks. dist., with healed blaze. |
| | A maple, 32 ins. diam., bears N. 66° W., 25 lks. dist., with healed blaze. |
| | Land, mountainous. |
| | Soil, shallow rocky clay loam. |