

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines
18002 T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Timber, fir, cedar, alder, hemlock, maple, and willow;
 undergrowth, vine maple, huckleberry, salmonberry
 poison oak, Oregon grape, salal, ferns, and grasses.

Subdivision of Section 10,
 T. 20 S., R. 9 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 10 and 15, monumented with
 an iron post, 1 in. diam., firmly set, projecting 8 ins.
 above with brass cap mkd.

1/4 $\frac{S\ 10}{S\ 15}$
 1954

from which an original bearing tree

A maple, 60 ins. diam., bears S. 87½° W., 66 lks.
 dist., no marks visible.

and a bearing tree mkd. by Tillman and Gawron

A fir, 50 ins. diam., bears N. 28½° W., 39 lks.
 dist., with healed blaze.

N. 0° 12' E., on the N. and S. center line of sec. 10,
 marking and blazing the true line.

Ascend over SE. slope, through heavy timber and dense
 undergrowth.

0.45 Top of ascent, slope E.; desc. over NE. slope.

1.40 Creek, 2 lks. wide, course S. 75° E.; asc. over SE.
 slope.

8.80 Spur, slopes S. 70° E, also leave timber, edge bears NW.
 and SE., enter old logged area; desc. over broken NE.
 slope.

28.75 Gravelled road, 15 lks. wide, bears N. 15° W. and
 S. 25° E., also enter timber, edge bears SE. and SW.

32.00 Creek, 10 lks. wide, course S. 20° E.; asc. over SW.
 slope.

39.25 Spur, slopes S. 80° W.; desc. over NW. slope.

39.39 Point for the center 1/4 sec. cor. of sec. 10, at inter-
 section with the E. and W. center line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T 20 S R 9 W
 C ¼ S 10
 1984

from which

A fir, 8 ins. diam., bears N. 17¼° E., 121 lks.
 dist., mkd. C¼ S10 BT.