

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 10, 18003
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A maple, 6 ins. diam., bears N. 60½° W., 22½ lks. dist., mkd. C¼ S10 BT.

Continue descent over NW. slope.


40.55 Creek, 2 lks. wide, course S. 50° W.; asc. over SE. slope.

42.75 Spur, slopes S. 20° W.; asc. over SW. slope.

59.00 Top of ascent, slopes W.; desc. over NW. slope.

68.00 Creek, 3 lks. wide, course S. 70° W.; asc. over SE. slope.

76.93 The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.



from which a bearing tree mkd. by person(s) unknown


A fir, 41 ins. diam., bears S. 41½° W., 38 lks. dist., with scribe mark S visible on opened blaze.

and a new bearing tree

A fir, 41 ins. diam., bears S. 36° W., 51 lks. dist., mkd. ¼ S10 BT.

No other suitable trees available.

From the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground (alongside of which is a rusted iron pipe 1 in. diam., firmly set, projecting 4 ins. above ground), with brass cap mkd.



from which the remains of bearing trees mkd. by Tillman and Gawron

A sawed fir stump, 40 ins. diam., bears S. 16½° E., 52 lks. dist., no marks visible. (Record, S. 25° E., 49 lks.)

A sawed fir stump, 42 ins. diam., bears N. 50½° W., 77 lks. dist., with scribe marks ¼ S10 BT visible on partially healed blaze.

and a new bearing tree

A hemlock, 7 ins. diam., bears N. 8½° E., 57 lks. dist., mkd. ¼ S11 BT.

No other suitable trees available.