

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 22,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

18005

CHAINS

$\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$
1953

from which the remains of an original bearing tree

A decayed fir snag, 33 ins. diam., bears
S. $64\frac{1}{2}^\circ$ W., 300 lks. dist., no marks visible.

and a bearing tree mkd. by Tillman and Gawron

A fir, 18 ins. diam., bears S. 80° E., 25 lks.
dist., with healed blaze.

and a bearing tree mkd. by person(s) unknown

A fir, 20 ins. diam., bears N. $44\frac{1}{2}^\circ$ W., 19 lks.
dist., with healed blaze.

N. $0^\circ 29'$ E., on the N. and S. center line of sec. 22.

Ascend over nearly level ground, through heavy timber
and dense undergrowth.

5.60 Top of ascent, slopes N. 45° W.; desc. over NW. slope.

10.75 Ravine, drains S. 55° W.; asc. over SW. slope.

15.60 Top of ascent, slopes SW.; desc. over NW. slope.

18.95 Creek, 2 lks. wide, course S. 20° W.; asc. over SE.
slope.

19.945 Point for the center S $\frac{1}{16}$ sec. cor. of sec. 22.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

C
 S $\frac{1}{16}$ | S 22
 C
 1984

from which

A fir, 30 ins. diam., bears N. $86\frac{1}{2}^\circ$ E., 88 lks.
dist., mkd. X BT.

A fir, 23 ins. diam., bears N. 18° W., $39\frac{1}{2}$ lks.
dist., mkd. CS $\frac{1}{16}$ S22 BT.

Continue ascent over broken SE. slope.

39.89 Point for the center $\frac{1}{4}$ sec. cor. of sec. 22, at inter-
section with the E. and W. center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 20 S R 9 W
 C $\frac{1}{4}$ S 22
 1984

from which