

County Surveyor's Record, Douglas County, Oregon

18006

Subdivision of Section 22,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| | <p>A fir, 6 ins. diam., bears S. 69½° W., 21 lks. dist. mkd. C¼ S22 BT.</p> <p>A fir, 4 ins. diam., bears N. 40° W., 16½ lks. dist., mkd. X BT.</p> <p>Continue ascent over SE. slope.</p> |
| 41.45 | <p>Saddle in spur ridge, bears N. 60° E. and S. 60° W., also gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.; desc. over NW. slope.</p> |
| 48.50 | <p>Ravine, drains S. 80° W.; asc. over SW. slope.</p> |
| 54.60 | <p>Dirt road, 15 lks. wide, bears N. 75° W. and S. 75° E.</p> |
| 57.20 | <p>Gravelled road, 20 lks. wide, bears N. 70° W. and S. 80° E.</p> |
| 58.85 | <p>Spur, slopes NW.; desc. over broken NW. slope.</p> |
| 76.10 | <p>Spur, slopes, N. 50° W.; desc. over NE. slope.</p> |
| 79.75 | <p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\frac{1}{4} \begin{array}{c} S 15 \\ S 22 \\ 1953 \end{array}$ </div> <p>from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A fir snag, 55 ins. diam., bears N. 54° W., 50 lks. dist., with scribe marks ¼ S visible on bark.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A sawed fir stump, 36 ins. diam., bears S. 72½° E., 73 lks. dist., mkd. ¼ S22 BT.</p> <p style="margin-left: 40px;">A cedar, 35 ins. diam., bears N. 30° W., 80 lks. dist., mkd. ¼ S15 BT.</p> <p>From this point, Lane County Public Works Department triangulation station "ROMAN 2 ECC 1973" bears N. 9° 30' E., 475.29 chs. dist., monumented with an iron post, 2½ in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. ROMAN 2 ECC 1973.</p> |
| | <p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>S. 89° 32' W., on the E. and W. center line of sec. 22.</p> <p>Descend over SW. slope, through heavy timber and dense undergrowth.</p> |
| 0.70 | <p>Creek, 2 lks. wide, course S. 45° E.; asc. over broken NE. slope.</p> |
| 2.20 | <p>Gravelled road, 20 lks. wide, bears N. 55° W. and S. 55° E.</p> |