

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 22,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

18007

**CHAINS**

19.75

Point for the center E 1/16 sec. cor. of sec. 22.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$C \frac{E \ 1/16}{S \ 22} C$$

1984

from which

A fir, 8 ins. diam., bears S. 53° W., 21 lks. dist., mkd. CE 1/16 S22 BT.

A fir, 5 ins. diam., bears N. 23° W., 29½ lks. dist., mkd. X BT.

Continue ascent over NE. slope, changing to E. slope.

25.10

Ridge, bears N. 10° W. and S. 10° E., also gravelled road, 20 lks. wide, bears same; desc. over SW. slope.

30.65

Head of ravine, drains S. 5° W.; asc. over SE. slope.

39.50

The center 1/4 sec. cor. of sec. 22.

Continue ascent over SE. slope.

40.60

Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.

43.00

Ridge, bears N. 65° E. and S. 60° W.; desc. over broken NW. slope.

58.00

Ravine, drains N. 15° W.; asc. over broken NE. slope.

68.35

Spur, slopes N.; desc. over NW. slope, changing to N. slope.

79.01

The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground with brass cap mkd.

$$S \ 21 \ \uparrow \ S \ 22$$

1953

from which the remains of the original bearing trees

A fir, 27 ins. diam., bears S. 39½° E., 23 lks. dist., with scribe marks ¼ S BT visible on bark.

A fir snag, 33 ins. diam., bears S. 62° W., 10 lks. dist., with scribe marks ¼ S BT visible on bark.

and a bearing tree mkd. by Tillman and Gawron

A fir, 50 ins. diam., bears S. 85° W., 18 lks. dist., with healed blaze.

From the E 1/16 sec. cor. of secs. 22 and 27, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.