

County Surveyor's Record, Douglas County, Oregon

18009

Subdivision of Section 22,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- 15.20 Gravelled road, 25 lks. wide, bears N. 30° W. and S. 30° E.
- 19.69 The SE 1/16 sec. cor. of sec. 22.
Continue descent over broken SW. slope.
- 31.45 spur, slopes SW.; desc. over NW. slope.
- 39.00 Creek, 2 lks. wide, course S. 20° W.; asc. over SE. slope.
- 39.39 The center S 1/16 sec. cor. of sec. 22.

Subdivision of Section 33,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

1/4 S 33
1953

from which a bearing tree mkd. by Tillman and Gawron

A fir, 17 ins. diam., bears N. 18° E., 8 lks. dist., with healed blaze.

and a bearing tree mkd. by Peterson

A fir, 7 ins. diam., bears N. 65° W., 15½ lks. dist., with healed blaze. (Record, 18 lks.)

and a new bearing tree

A fir, 35 ins. diam., bears N. 28° W., 52 lks. dist., mkd. 1/4 S33 BT.

N. 6° 16' W., on the N. and S. center line of sec. 33.

Ascend over SE. slope, through heavy timber and dense undergrowth.

- 1.25 Spur, slopes E.; desc. over NE. slope.
- 7.15 Ravine, drains N. 80° E.; asc. over SE. slope.
- 11.45 Spur, slopes E.; desc. over NE. slope.
- 20.47 Point for the center S 1/16 sec. cor. of sec. 33.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S 33
C
1984

from which