

# County Surveyor's Record, Douglas County, Oregon

**18010**

Subdivision of Section 33,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 24 ins. diam., bears S.  $38\frac{1}{2}^\circ$  E., 78 lks.  
dist., mkd. CS 1/16 S33 BT.

A fir, 17 ins. diam., bears N.  $30\frac{1}{4}^\circ$  W.,  $87\frac{1}{2}$  lks.  
dist., mkd. X BT.

Continue descent over NE. slope.

21.35 Ravine, drains N.  $80^\circ$  E.; asc. over SE. slope.

22.45 Spur, slopes N.  $80^\circ$  E.; desc. over NE. slope.

33.90 Bottom of descent, slopes E.; asc. over SE. slope.

38.55 Spur, slopes N.  $60^\circ$  E.; desc. over NW. slope.

40.94 Point for the center 1/4 sec. cor. of sec. 33, at inter-  
section with the E. and W. center line.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 20 S R 9 W  
C  $\frac{1}{4}$  S 33  
1984

from which

A fir, 32 ins. diam., bears N.  $63\frac{1}{4}^\circ$  E., 79 lks.  
dist., mkd. C $\frac{1}{4}$  S33 BT.

A cedar, 25 ins. diam., bears S.  $72^\circ$  W., 106 lks.  
dist., mkd. C $\frac{1}{4}$  S33 BT.

Continue descent over NW. slope.

44.00 Left bank of Smith River, bears N.  $80^\circ$  E. and S.  $85^\circ$  W.,  
course W.; thence across river.

46.00 Right bank of Smith River, bears E. and W.; asc. over  
nearly level ground.

51.50 Smith River Road, asphalt surface, 40 lks. wide, bears  
N.  $75^\circ$  E. and S.  $75^\circ$  W.; asc. over SE. slope.

56.10 Gravelled road, 35 lks. wide, bears N.  $60^\circ$  W. and  
S.  $60^\circ$  E.

61.12 Point for the center N 1/16 sec. cor. of sec. 33.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

C  
N 1/16 | S 33  
C  
1984

from which

A fir, 27 ins. diam., bears S.  $51\frac{1}{2}^\circ$  E., 84 lks.  
dist., mkd. CN 1/16 S33 BT.

A fir, 60 ins. diam., bears N.  $77\frac{1}{2}^\circ$  W., 65 lks.  
dist., mkd. X BT.