

# County Surveyor's Record, Douglas County, Oregon

**18012**

Subdivision of Section 33,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

$\frac{1}{4}$   
 S 32 | S 33  
 1953

from which the remains of the original bearing trees

A cedar snag, 64 ins. diam., bears N. 49½° E., 113 lks. dist., with healed blaze.

A cedar, 68 ins. diam., bears S. 21½° W., 43 lks. dist. with healed blaze.

and bearing trees mkd. by Tillman and Gawron

A fir, 20 ins. diam., bears N. 35½° E., 39 lks. dist., with healed blaze. (Record N. 39° E., 44 lks.)

A fir, 26 ins. diam., bears S. 40 3/4° W., 70 lks. dist., with healed blaze.

and a bearing tree mkd. by Chatters

A cedar, 20 ins. diam., bears S. 32 3/4° E., 39 lks. dist., no marks visible. Remark 1/4 S33 BT. (Record, S. 31° E.)

From the center E 1/16 sec. cor. of sec. 33.

N. 3° 03' W., on the N. and S. center line of the NE¼ of sec. 33.

Descend over NE. slope, through heavy timber and dense undergrowth.

7.30 Vincent Creek, 30 lks. wide, course N. 40° W.; asc. over broken SW. slope.

14.20 Ravine, drains S. 70° W.; continue ascent over SW. slope.

20.07 Point for the NE 1/16 sec. cor. of sec. 33, at intersection with the E. and W. center line of the NE¼.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S 33  
1984

from which

A fir, 15 ins. diam., bears N. 66½° E., 30 lks. dist., mkd. NE 1/16 S33 BT.

A fir, 28 ins. diam., bears S. 39° W., 54 lks. dist., mkd. X BT.

Continue ascent over SW. slope.

22.25 Spur, slopes W.; desc. over NW. slope.

23.85 Ravine, drains W.; asc. over SW. slope.

26.10 Spur, slopes W.; desc. over NW. slope.