

County Surveyor's Record, Douglas County, Oregon

18013

Subdivision of Section 33,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
31.70	Creek, 1 lk. wide, course S. 80° W.; asc. over SW. slope.
34.70	Spur, slopes W.; desc. over NW. slope.
37.15	Ravine, drains S. 70° W.; asc. over SW. slope.
40.14	The E 1/16 sec. cor. of secs. 28 and 33.
<p>From the N 1/16 sec. cor. of secs. 33 and 34.</p> <p>S. 89° 14' W., on the E. and W. center line of the NE 1/4 of sec. 33.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p>	
2.20	Ridge, bears N. 45° W. and S. 45° E.; desc. over SW. slope.
10.00	Spur, slopes S. 45° W.; desc. over NW. slope.
19.95	Ravine, drains S. 50° W.; asc. over SE. slope.
21.85	Spur, slopes S. 20° W.; desc. over SW. slope.
23.27	The NE 1/16 sec. ocr. of sec. 33.
Continue descent over SW. slope, changing to W. slope.	
30.10	Left bank of Smith River, bears N. 10° W. and S. 10° E.; course S. 10° E., thence across river.
31.10	Right bank of Smith River, bears N. 10° W. and S. 10° E.
31.37	Intersect line 5-6 of Lot 7.
No permanent monument established.	
Continue over nearly level ground.	
33.385	Intersect line 3-4 of lot 7.
No permanent monument established.	
34.00	Smith River Road, asphalt surface, 35 lks. wide, bears N. 10° E. and S. 20° W., in curve; begin ascent over SE. slope.
46.55	The center N. 1/16 sec. cor. of sec. 33.
<p>From the E 1/16 sec. cor. of sec. 33 only, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"><u>E 1/16 S 33</u> 1966</p> <p>from which bearing trees mkd. by Peterson</p> <p style="padding-left: 40px;">A maple, 27 ins. diam., bears N. 71° E., 40 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 32 ins. diam., bears N. 62° W., 22 lks. dist., with healed blaze.</p>	