




County Surveyor's Record, Douglas County, Oregon

18016

Survey of Lot 7 in Section 33,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
6.864	<p>(453.0 ft.) Point for angle point No. 3, Lot 7.</p> <p>Set an iron post, 28 ins. long 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">_____</p> <p>Thence N. 7° 30' E., along line 3-4, Lot 7.</p>
0.90	<p>North end of road, asphalt surface, 10 lks. wide, bears S. 30° W.</p>
3.273	<p>Intersect the E. and W. center line of the NE 1/4 of sec. 33.</p>
5.576	<p>(368.0 ft.) Point for angle point No. 4, Lot 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">_____</p> <p>Corner is located on W. edge of cleared area, bears NW. and SW.</p> <p style="text-align: center;">_____</p> <p>Thence East, along Line 4-5, Lot 7.</p>
0.70	<p>Leave cleared area, edge bears N. 5° W. and S. 5° E., enter timber and dense undergrowth.</p>
1.515	<p>(100.0 ft.) Point for angle point No. 5, Lot 7.</p> <p>Seat a brass tablet, 3¼ ins. diam., 3½ ins. stem, in drill hole, in solid rock, with top mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">_____</p> <p>Corner is located on right bank of Smith River, bears N. 10° W. and S. 10° E.</p> <p style="text-align: center;">_____</p> <p>Thence S. 5° 00' E., along line 5-6, Lot 7.</p>
2.265	<p>Intersect the E. and W. center line of the NE¼ of sec. 33.</p>
4.848	<p>(320.0 ft.) Point for angle point No. 6, Lot 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>