

County Surveyor's Record, Douglas County, Oregon

18026

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

No suitable tree available in Sec. 3.

S. 89° 49' W., bet. secs. 4 and 9.

Ascend over SE. slope, through light timber and moderate undergrowth.

6.70 Spur, slopes N. 70° E.; desc. over NW. slope.

19.50 Creek, 2 lks. wide, course N. 25° E.; asc. over NE. slope.

39.93 The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 24 S
	S 4
1/4	<u> </u>
	S 9
	R 4 W
	1963

from which the bearing trees mkd. by Jelley

A chinquapin, 8 ins. diam., bears N. 4 1/2° E.,
22 1/2 lks. dist., with scribe marks 1/4 S4 BT
visible on bark blaze.

A chinquapin, 10 ins. diam., bears S. 42 1/2° E.,
15 1/2 lks. dist., with scribe marks 1/4 S9 BT
visible on bark blaze.

S. 89° 50' W., beginning new measurement.

Ascend over NE slope.

37.10 Rocky ridge, bears N. 15° W. and S. 25° E.; desc. over SW. slope.

41.48 The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 24 S	
	S 5	S 4
	<u> </u>	<u> </u>
	S 8	S 9
	R 4 W	
	1963	

from which the remaining original bearing trees

A fir, 60 ins. diam., bears N. 40° E.,
49 lks. dist., with healed blaze, and
fragmentary scribe marks visible on bark.

A madrone, 16 ins. diam., bears S. 18° W.,
86 lks. dist., no marks visible on opened
blaze.

and bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor in 1963

A fir, 11 ins. diam., bears S. 14° E.,
54 1/2 lks. dist., with healed blaze.