

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 4 W., Willamette Meridian, Oregon 18027

CHAINS

A fir, 10 ins. diam., bears S. 61° W.,
39 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears N. 78° W.,
38 lks. dist., with healed blaze.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, cedar, hemlock, maple, oak, madrone,
chinquapin, and ash; undergrowth, salal, vinemaple,
poison oak, and fern.

Subdivision of Section 9, T. 24 S., R. 4 W.
Willamette Meridian, Oregon

From the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with
an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8
ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
 $\frac{1}{4}$ $\frac{S 9}{S 16}$
R 4 W
1963

from which the remaining original bearing tree

A maple, 28 ins. diam., bears N. 19° W.,
14 lks. dist., no marks visible on opened
blaze.

and bearing trees mkd. by Milo E. Godfrey, Deputy County
Surveyor in 1963

A cedar, 15 ins. diam., bears N. 44° E.,
45 $\frac{1}{2}$ lks. dist., with healed blaze.

A cedar, 9 ins. diam., bears S. 36° W.,
26 lks. dist., with healed blaze.

N. 0° 18' E., on the N. and S. center line of sec. 9.

Ascend over S. slope, through heavy timber and dense
undergrowth.

19.90 Point for the center S $\frac{1}{16}$ sec. cor. of sec. 9

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in
the ground, with brass cap mkd.

C
S $\frac{1}{16}$ | S 9
C
1984

from which

A fir, 13 ins. diam., bears S. 39 $\frac{1}{2}$ ° E.,
55 lks. dist., mkd. CS $\frac{1}{16}$ S9 BT.

A fir, 8 ins. diam., bears N. 83 $\frac{3}{4}$ ° W.,
18 lks. dist., mkd. CS $\frac{1}{16}$ S9 BT.

Ascend over S. slope.

31.00 Head of Ravine, drains S. 30° E.; asc. over SW. slope.