

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 9, T. 24 S., R. 4 W., 18029
Willamette Meridian, Oregon

CHAINS

58.30

Gravel road, 15 lks. wide, bears N. 15° W. and S. 15° E.

60.47

Point for the center W 1/16 sec. cor. of sec. 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

W 1/16
S 9
1984

from which

A fir, 9 ins. diam., bears S. 8½° W.,
48 lks. dist., mkd. CW 1/16 S9 BT.

A fir, 17 ins. diam., bears N. 17 ¾° W.,
9 lks. dist., mkd. CW 1/16 S9 BT.

Ascend over SE. slope.

75.75

Spur, slopes S. 25° E.; desc. over SW. slope.

78.95

Rock bluff, 40 ft. high; desc. over SW. slope.

81.16

The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 24 S R 4 W
S 8 | S 9
1979

from which a bearing tree and a bearing object mkd. by Jelley

A basalt boulder, 6 x 6 x 5 ft. above ground,
bears N. 53½° E., 33½ lks. dist., with marks
X BO visible on W. face.

A fir, 8 ins. diam., bears S. ½° W., 12 lks.
dist., with healed blaze.

From the W 1/16 sec. cor. of secs. 9 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

W 1/16 S 9
S 16
1979

from which bearing trees mkd. by Donald A. Bentz,
Registered Land Surveyor, No. 839, in 1979

A cedar, 7 ins. diam., bears N. 51° E.,
25 lks. dist., with scribe marks 1/16 S9 BT
visible on a partially healed blaze.

An oak, 13 ins. diam., bears S. 49° E.,
11½ lks. dist., with scribe marks 1/16 S16 BT
visible on a partially healed blaze.

and a bearing object mkd. by Jelley

A basalt boulder, 15 x 12 x 8 ft. above ground
bears S. 13° E., 6½ lks. dist., with marks
X BO visible on NW. face.