

County Surveyor's Record, Douglas County, Oregon

18030 Subdivision of Section 9, T. 24 S., R. 4 W.
Willamette Meridian, Oregon

CHAINS	
	<p>N. 0° 12' E., on the N. and S. center line of the SW$\frac{1}{4}$ of Sec. 9.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p>
18.55	<p>Spur, slopes S. 70° E.; asc. over SE. slope.</p>
19.92	<p>Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set an aluminum post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16 S 9 1984</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 1 3/4° W., 21 lks. dist., mkd. SW 1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 72$\frac{1}{2}$° W., 7 lks. dist., mkd. X BT.</p> <p>Ascend over SE. slope.</p>
39.83	<p>The center W 1/16 sec. cor. of sec. 9.</p>
	<p>From the center S 1/16 sec. cor. of sec. 9.</p> <p>S. 89° 49' W., on the E. and W. center line of the SW$\frac{1}{4}$ of sec. 9.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p>
9.00	<p>Spur, slopes S.; desc. over SE. slope.</p>
12.70	<p>Creek, 2 lks. wide, course S. 5° W.; asc. over SE. slope.</p>
18.70	<p>Spur, slopes S. 70° E.; desc. over SW. slope.</p>
20.65	<p>The SW 1/16 sec. cor. of sec. 9.</p> <p>Descend over SW. slope</p>
41.30	<p>The S 1/16 sec. cor. of secs. 8 and 9, monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, in a collar of stone 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 8 S 9 1979</p> <p>from which bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 74° E., 44$\frac{1}{2}$ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A grand fir, 16 ins. diam., bears S. 45$\frac{1}{2}$° W., 47 lks. dist., with healed blaze.</p>