

County Surveyor's Record, Douglas County, Oregon

18034

Dependent Resurvey of a Portion of the South Boundary
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp., perpetuated by Wilford N. Haines, Registered Land Surveyor No. 239, during an unrecorded survey, year unknown, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above ground, with a washer, 1 in. diam., mkd.

Wilford N. Haines
239
Survey Point
Drain Oregon

(SEE P.O. H-64)

from which the remains of an original bearing tree

A decayed chinquapin snag, 18 ins. diam., bears S. 22°W., 49 lks. dist., with axe marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with aluminum cap mkd.

T 20 S R 7 W
S 34 S 35
S 3
T 21 S R 7 W
1983

from which new bearing trees

A fir, 11 ins. diam., bears N. 78½° E., 20 lks. dist., mkd. T20S R7W S35 BT.

A fir, 10 ins. diam., bears N. 38½° W., 28 lks. dist., mkd. X BT.

S 88° 14' W., on the S. bdy. of sec. 34, marking and blazing the true line.

Descend over NW. slope, through heavy timber and dense undergrowth.

- 6.15 Creek, 3 lks. wide, course S. 30° W.; asc. over broken SE. slope.
 - 9.25 Spur, slopes S.; desc. over broken SW. slope.
 - 11.20 Creek, 5 lks. wide, course S. 40° E; asc. over broken NE. slope.
 - 18.55 Spur, slopes NE.; desc. over NW. slope.
 - 22.41 Point for the 1/4 sec. cor. of sec. 3 only, T. 21 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 20 S R 7 W
1/4 S 3
T 21 S R 7 W
1984

from which