

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

18035

CHAINS	
	<p>A fir, 7 ins. diam., bears S. 56° E., 66 lks. dist., mkd. 1/4 S 3 BT.</p> <p>A hemlock, 5 ins. diam., bears S. 72° W., 29 lks. dist., mkd. 1/4 S 3 BT.</p> <p>Descend over NW. slope.</p>
25.05	Ravine, drains N. 60° E.; asc. over SE. slope.
29.80	Spur, slopes S. 60° E.; desc. over broken SW. slope.
39.41	<p>The 1/4 sec. cor. of sec. 34 only, perpetuated and recorded Wilford N. Haines, Registered Land Surveyor No. 239, in 1965, further perpetuated and recorded by Gary L. Langlitz, Deputy County Surveyor, in 1974, monumented with the original sandstone, 24 x 24 ins. x 2 ft. above ground, mkd. X on top, from which the remains of a bearing tree and a reference monument mkd. by Haines:</p> <p style="padding-left: 40px;">A 1 in. "T" shaped iron rod, firmly set, projecting 10 ins. above ground, bears North, 2 lks. dist., with a washer, 1 in. diam., mkd. Wilford N. Haines 239 Survey Point Drain Oregon.</p> <p style="padding-left: 40px;">A sawed fir stump, 34 ins. diam., bears N. 77° W., 151 lks. dist., with scribe marks BT visible on open blaze.</p> <p>and the remains of a bearing tree mkd. by Langlitz</p> <p style="padding-left: 40px;">A sawed fir stump, 32 ins. diam., bears N. 19° W., 151 lks. dist., with healed blaze.</p> <p>Seat a brass tablet, 3½ ins. diam., 3¼ ins. stem, in drill hole at point of the X in the corner stone, with brass tablet mkd.</p> <p style="text-align: center;">T 20 S R 7 W ½ S 34 T 21 S R 7 W 1983</p> <p>from which a new bearing tree and bearing object</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 87½° E., 13 lks dist., mkd. X BT.</p> <p style="padding-left: 40px;">A rock outcrop, 10 x 10 ft. bears N. 26° W., 116 lks. dist., mkd. X B0.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 29' W., beginning new measurement.</p> <p>Descend over SW. slope.</p>
0.40	Ravine, drains SE.; asc. over SE. slope.
9.65	Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.
10.70	Spur, slopes S.; desc. over SW. slope.
11.50	Gravelled road, 20 lks. wide, bears N. 20° W. and S. 20° E.