

County Surveyor's Record, Douglas County, Oregon

18038

Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 20 S R 7 W

½ S 4
T 21 S R 7 W
1984

from which new bearing trees

A fir, 10 ins. diam., bears S. 7 ¾° E.,
16 lks. dist., mkd. ½ S4 BT.

A fir, 8 ins. diam., bears S. 83½° W.,
41 lks. dist., mkd. X BT.

S. 88° 06' W., beginning new measurement.

Descend over SW. slope.

1.60 Head of ravine, drains N. 15° W.; desc. over broken NW slope.

8.60 Gravelled road, 20 lks. wide, bears N. and S.

16.86 Point for the ¼ sec. cor. of sec. 33 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W

¼ S 33
T 21 S R 7 W
1984

from which

A fir, 8 ins. diam., bears N. 12½° E., 3½ lks. dist., mkd. ¼ S33 BT.

An alder, 8 ins. diam., bears N. 82½° W.,
43 lks. dist., mkd. ¼ S33 BT on bark.

Descend over broken NW. slope, changing to SW. slope.

36.70 Smith River, 65 lks. wide, course S. 10° E.; asc. over broken NE. slope.

40.95 The cor. of secs. 4 and 5 only, T. 21 S., R. 7 W., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, 1962, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

S 5 | S 4
T 21 S R 7 W
1962

from which the remains of an original bearing tree