

County Surveyor's Record, Douglas County, Oregon

18039

Dependent Resurvey of a Portion of the South Boundary
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 67 ins. diam., bears
S. 37° W., 20 lks. dist., no marks visible.

and bearing trees mkd. by persons unknown and recorded by
Godfrey

A cedar, 29 ins. diam., bears N. 84° W.,
32 lks. dist., with fragmentary scribe marks
visible on opened blaze.

A hemlock, 38 ins. diam., bears N. 24½° W.,
21 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.

and a bearing tree mkd. by Godfrey

A fir, 17 ins. diam., bears S. 78½° E.,
29 lks. dist., with healed blaze.

From this point, a point established by Wilford N.
Haines, Registered Land Surveyor, No. 239, during an
unrecorded survey, bears N. 18½° W., 0.06 chs. dist.,
monumented with a 1 in. "T" shaped iron rod, firmly set,
projecting 5 ins. above ground.

*(SEE
F.O. H-64
FOR POSSIBLE
INFO.)*

S. 89° 12' W., beginning new measurement.

Ascend over broken NE. slope.

- 1.60 Paved road, 30 lks. wide, bears N. 40° W. and
S. 40° E.
- 10.60 Spur, slopes N. 10° W.; desc. over NW. slope.
- 14.10 The cor. of secs. 32 and 33, perpetuated by Wilford N.
Haines, Registered Land Surveyor, No. 239, subsequently
perpetuated and recorded by Milo E. Godfrey, Deputy
County Surveyor, in 1962, monumented with a 1 in. "T"
shaped iron rod, firmly set, projecting 4 ins. above
ground, from which the remains of an original bearing
tree:

A decayed fir stump, size indeterminate,
bears S. 27° W., 19 lks. dist., no marks
visible.

and bearing trees mkd. by Godfrey

A hemlock, 12 ins. diam., bears N. 57½° E.,
69 lks. dist., with healed double blaze.

A hemlock, 12 ins. diam., bears N. 58° W.,
37½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in
the ground, directly over the iron rod, with brass cap
mkd.

T 20 S R 7 W
T 32 | S 33
S 5
T 21 S R 7 W
1983