

County Surveyor's Record, Douglas County, Oregon

18040 Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, yew, hemlock, cedar, alder, maple, ash,
chinquapin, cascara, willow, and cherry; undergrowth,
vine maple, poison oak, arrowwood, hazel, Oregon grape,
salal, ferns, blackberry, huckleberry, thimbleberry, wild
rose, and young timber.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 20 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Thomas E. Todd, in 1891)

From the cor. of secs. 34 and 35 only, on the S. bdy of
the tp.

N. 0° 28' W., bet. secs. 34 and 35, marking and blazing
the true line.

Ascend over SW. slope, through heavy timber and dense
undergrowth.

0.90 Spur, slopes S. 80° W.; desc. over broken NW. slope.

5.50 Ravine, drains S. 70° W.; asc. over broken SE. slope.

26.95 Ridge, bears N. 80° E. and S. 80° W.; desc. over broken
NE. slope.

36.40 Spur, slopes NE.; desc. over NW. slope.

39.71 Point for the 1/4 sec. cor. of secs. 34 and 35 at
proportionate distance; there is no remaining evidence of
the original corner.

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T 20 S R 7 W
 ½
 S 34 | S 35
 1984

from which

A fir, 5 ins. diam., bears S. 61½° E.,
10 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 67½° W.,
36 lks. dist., mkd. ¼ S34 BT.

Descend over NW. slope.

45.30 Ravine, drains N. 80° E.; asc. over SE. slope.

49.20 Spur, slopes N. 70° E.; desc. over NW. slope.

64.45 Smith River, 50 lks. wide, course S. 55° W.; asc.
over broken SE. slope.

68.80 Paved road, 40 lks. wide, bears N. 65° E. and S. 65° W.

77.60 Spur, slopes S. 35° W.; desc. over NW. slope.