

County Surveyor's Record, Douglas County, Oregon

18042

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 20S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 9 ins. diam., bears S. 59 $\frac{1}{4}$ ° E.,
28 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears N. 89° W.,
10 $\frac{1}{2}$ lks. dist., with healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, directly over the iron rod, with
aluminum cap mkd.

T 20 S R 7 W
 $\frac{1}{4}$
S 33 | S 34
1983

Land, mountainous.
Soil, rocky clay.
Timber, fir, cedar, alder, yew, and maple; undergrowth,
vine maple, poison oak, blackberry, salal, hazel,
arrowwood, Oregon grape, ferns, wild rose, and young timber.

From the cor. of secs. 32 and 33 only, on the S. bdy. of
the Tp.

N. 0° 36' W., bet. secs. 32 and 33.

Descend over NW. slope, through heavy timber and dense
undergrowth.

8.10 Paved road, 30 lks. wide, bears N. 60° E. and S. 55° W.

18.05 Smith River 65 lks. wide, course N. 60° E.; asc. over
SE. slope.

26.10 Spur, slopes S. 55° W.; desc. over NW. slope.

38.62 The 1/4 sec. cor. of secs. 32 and 33, perpetuated and
recorded by Wilford N. Haines, Registered Land Surveyor
No. 239, in 1961 and 1965, and further perpetuated and
recorded by Milo E. Godfrey, Deputy County Surveyor, in
1962, monumented with a 1 in. "T" shaped iron rod, firmly
set, projecting 4 ins. above ground, from which the
remains of an original bearing tree:

A roothole, bears N. 70° E., 23 lks. dist.,
with a down fir alongside, size indeterminate,
no marks visible. (Record, S. 17° E)

and the remains of a bearing tree mkd. by Godfrey

A sawed cedar stump, 40 ins. diam., bears
N. 68° E., 36 lks. dist., with scribe marks
 $\frac{1}{4}$ S33, BT visible on open double blaze.

and the remains of a bearing tree mkd. by Haines in 1965

A hemlock snag, 26 ins. diam., bears N. 62° W.,
249 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{4}$ ins. diam., 24 ins. in
the ground, directly over the iron rod, with brass cap
mkd.