

County Surveyor's Record, Douglas County, Oregon

11 18043

Dependent Resurvey of a Portion of the Subdivisional
Lines T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

T 20 S R 7 W

S 32 | S 33
1984

from which new bearing trees

A fir, 8 ins. diam., bears N. 58° E., 37½ lks.
dist., mkd. ¼ S33 BT.

A fir, 6 ins. diam., bears N. 40° W., 30½ lks.
dist., mkd. S BT.

N. 0° 13' W., beginning new measurement.

Descend over NW. slope.

18.35 Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.

22.15 Smith River, 65 lks. wide, course S. 50° W.; asc. over
SE slope.

24.10 Paved road, 40 lks. wide, bears N. 60° E. and S. 65° W.

40.44 The cor. of secs. 28, 29, 32, and 33 monumented with an
iron post, 2½ ins. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

T 20 S R 7 W

S 29 | S 28
S 32 | S 33
1967

from which the remaining original bearing tree

A hemlock, 24 ins. diam., bears S. 31° E.,
5 lks. dist., with scribe marks W S 33 visible
on opened blaze.

and the remains of bearing trees mkd. by Wilford N.
Haines, Registered Land Surveyor No. 239, in 1961

A cedar stump, 23 ins. diam., bears S. 46° W.,
42 lks. dist., with a metal disc, 1 in. diam.,
mkd. Wilford N. Haines 239 Survey Point Drain
Oregon attached. (Record, S. 54° W.)

A fir, 53 ins. diam., bears N. 35° W.,
79 lks. dist., with scribe marks T20S R7W
S29 BT visible on bark blaze.

and the remains of a bearing tree mkd. by Milo E
Godfrey, Deputy County Surveyor, in 1962

A sawed cedar stump, 52 ins. diam., bears
S. 52° W., 61 lks. dist., with scribe marks
T20S R7W S32 BT visible on partially healed
double blaze.

and a bearing tree mkd. by Roseberry and Glenn, in 1967

A fir, 35 ins. diam., bears N. 59° E.,
167 lks. dist., with healed blaze. (Record,
172 lks. dist.)

and a new bearing tree