

County Surveyor's Record, Douglas County, Oregon

18044 ¹²

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 23 ins. diam., bears S. 26° W.,
70 lks. dist., mkd. T20S R7W S32 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, yew, hemlock, alder, maple, chinquapin,
ash, willow, cedar; undergrowth, vine maple, poison oak,
thimbleberry, blackberry, arrowwood, hazel, salal, ferns,
huckleberry, Oregon grape, and young timber.

From the cor. of secs. 27, 28, 33, and 34, perpetuated
and recorded by Wilford N. Haines, Registered Land
Surveyor No. 239, in 1965, monumented with a 1 in. "T"
shaped iron rod, firmly set, projecting 10 ins. above
ground, from which the remains of an original bearing
tree:

A sawed fir stump, size indeterminate, bears
N. 42° E., 14 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Haines

A sawed hemlock stump, 18 ins. diam., bears
N. 8° E., 78 lks. dist., with healed blaze.

A sawed alder stump, 16 ins. diam., bears
S. 64° E., 16 lks. dist., with scribe marks
S34 T20S R7W BT visible on bark.

A sawed alder stump, 16 ins. diam., bears
S. 13° W., 48 lks. dist., with scribe marks
S33 T20S R7W BT visible on bark.

A sawed maple stump, size indeterminate, bears
N. 79 3/4° W. 79 lks. dist., no marks
visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, directly over the iron rod, with brass
cap mkd.

*FD OK 10/95 BY EDWARDS
M 122-71*

T 20 S R 7 W			
S 28	S 27		
S 33	S 34		
1983			

from which new bearing trees and reference monuments

An iron post, 28 ins. long, 2 1/2 ins. diam.,
set 24 ins. in the ground for a reference
monument, bears N. 40° E., 50 lks. dist.,
with brass cap mkd. RM T20S R7W S27 1984,
and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. diam.,
set 24 ins. in the ground, for a reference
monument, bears S. 40° E., 50 lks. dist.,
with brass cap mkd. RM T20S R7W S34 1984,
and an arrow pointing to the corner.

A fir, 19 ins. diam., bears S. 29 1/2° W.,
407 lks. dist., mkd. T20S R7W S33 BT.

A maple, 9 ins. diam., bears N. 11 3/4° W.,
568 lks. dist., mkd. T20S R7W S28 BT.