

County Surveyor's Record, Douglas County, Oregon

18045

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>From this point, United States Geological Survey, triangulation station "GUNTER 1940", bears N. 2° 43' E., 88.21 chs. dist., monumented with a standard brass tablet, 3½ ins. diam., set in a concrete post, 8 ins. diam., set flush with ground, with top mkd. U. S. Geological Survey GUNTER 1940 and a triangle.</p> <p>S. 88° 09' W., bet. secs. 28 and 33.</p> <p>Descend over nearly level land, through logged area.</p>
8.40	<p>Smith River, 65 lks. wide, course NE.; asc. over SE. slope, also enter timber, edge bears NE. and SW.</p>
19.45	<p>Point for the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <u>S 28</u> S 33 1984 </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 14 ins. diam., bears N. 7½° E., 43½ lks. dist., mkd. E 1/16 S28 BT.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 36° W., 25 lks. dist. mkd. E 1/16 S33 BT.</p> <p>Ascend over SE. slope.</p>
21.75	<p>Spur, slopes N. 40° W.; desc. over NW. slope.</p>
37.95	<p>Smith River, 65 lks. wide, course S. 25° W.; continue over nearly level river bottom.</p>
38.90	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 20 S R 7 W <u>S 28</u> S 33 1984 </div> <p>from which</p> <p style="margin-left: 40px;">An alder, 19 ins. diam., bears S. 73½° W., 55 lks. dist., mkd. 1/4 S33 BT.</p> <p style="margin-left: 40px;">A cedar, 46 ins. diam., bears N. 48 3/4° W., 197 lks. dist., mkd. ¼ S28 BT.</p> <p>Continue over nearly level river bottom.</p>
46.90	<p>Smith River, 65 lks. wide, course NW; asc. over NE. slope.</p>
50.95	<p>Spur, slopes N. 25° W.; desc. over NW. slope.</p>
58.35	<p>Point for the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>