

# County Surveyor's Record, Douglas County, Oregon

**18046**    Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<u>S 28</u> S 33 1984
	from which  A cedar, 23 ins. diam., bears N. 36° E., 108 lks. dist., mkd. W 1/16 S28 BT.  A maple, 14 ins. diam., bears S. 73 3/4° E., 44 lks. dist., mkd. W 1/16 S33 BT.  Continue over river bottom
59.85	Smith River, 65 lks. wide, course S. 5° E.; asc. over broken SE. slope.
62.75	Paved road, 40 lks. wide, bears N. 20° E. and S. 15° W.
70.65	Spur, slopes S.; desc. over SW. slope.
73.30	Creek, 3 lks. wide, course SE.; asc. over SE. slope.
77.30	Gravelled road, 20 lks. wide, bears N. and S.
77.80	The cor. of secs. 28, 29, 32, and 33.  Land, rolling terrain. Soil, rocky clay loam. Timber, fir, hamlock, cedar, yew, alder, ash, maple, willow, apple, cherry, and chinquapin; undergrowth, vine maple, hazel, arrowwood, blackberry, salal, thimbleberry, Oregon grape, huckleberry, ferns, hawthorne, and young timber.
Subdivision of Section 33, T. 20 S., R. 7 W. Willamette Meridian, Oregon	
	From the 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp.  N. 0° 08' E., on the N. and S. center line of sec. 33, marking and blazing the true line.  Descend over broken NW. slope, through heavy timber and dense undergrowth.
19.15	Creek, 5 lks. wide, course S. 60° W.; asc. over SE. slope.
35.25	Gravelled road, 20 lks. wide, bears N. 65° W. and S. 75° E.
35.65	Ridge, bears N. 65° W. and S. 75° E.; desc. over N. slope.
36.80	Head of ravine, drains NE.; asc. over SE. slope.
38.60	Spur, slopes NE.; desc. over NW. slope.
39.03	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.