

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 33, T. 20 S., R. 7 W.,  
Willamette Meridian, Oregon

15  
**18047**

CHAINS	T 20 S R 7 W C ¼ S 33 1984
	from which  A sandstone outcrop, 10 x 10 ft., bears N. 87½° E., 74 lks. dist., mkd. X B0.  A hemlock, 12 ins. diam., bears S. 82° W., 76 lks. dist., mkd. C¼ S33 BT.  A fir, 23 ins. diam., bears N. 21° W., 99 lks. dist., mkd. C¼ S33 BT.  Descend over NW. slope.
39.25	Ravine, drains NE.; asc. over SE. slope.
49.90	Spur, slopes NE.; asc. over broken NW. slope.
78.55	Smith River, 65 lks. wide, course S. 70° W.; continue over river bottom.
79.31	The 1/4 sec. cor. of secs. 28 and 33.
	From the 1/4 sec. cor. of secs. 33 and 34.  S. 87° 56' W., on the E. and W. center line of sec. 33.  Descend over NW. slope, through heavy timber and dense undergrowth.
6.65	Creek, 5 lks. wide, course N.; asc over NE. slope.
19.73	Point for the center E 1/16 sec. cor. of sec. 33.  Set an aluminum, post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	C $\frac{E \ 1/16}{S \ 33}$ C 1984
	from which  A cedar, 20 ins. diam., bears S. 2½° W., 15 lks. dist., mkd. CE 1/16 S33 BT.  A fir, 21 ins. diam., bears N. 33½° W., 25 lks. dist., mkd. CE 1/16 S33 BT.  Ascend over NE. slope.
20.05	Spur, slopes N. 10° W.; desc. over NW. slope.
38.05	Ravine, drains NE.; asc. over SE. slope.
39.06	Spur, slopes NE.; desc. over NW. slope.
39.46	The center 1/4 sec. cor. of sec. 33.  Descend over NW. slope.
39.85	Ravine, drains NE.; asc. over SE. slope.
44.50	Spur, slopes SE.; desc. over SW. slope, changing to NW. slope.