

County Surveyor's Record, Douglas County, Oregon

18054

Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

41.125

Point for the 1/4 sec. cor. of sec. 35 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 6 W
 $\frac{1}{4}$ S 35
 T 21 S R 6 W
 1984

*FD OK
12/92
L. Roberts
M116-43
C.S. 63/179*

from which

A fir, 21 ins. diam., bears N. 28° E., 45 lks. dist., mkd. ¼ S35 BT.

A fir, 22 ins. diam., bears N. 35½° W., 25 lks. dist., mkd. X BT.

Descend over SW. slope.

54.70

Smith River, 45 lks. wide, course NW.; continue over river bottom.

58.00

Smith River, 25 lks. wide, course S. 75° W.; continue over river bottom.

69.45

Smith River, 40 lks. wide, course N. 35° W.; continue over river bottom.

78.64

True point for the closing cor. of secs. 2 and 3, hereinafter described.

Continue over river bottom.

82.25

The cor. of secs. 34 and 35, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1954, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 20 S R 6 W
 $\frac{34}{3} \mid \frac{35}{3}$
 T 21 S R 6 W
 1954

from which the remains of the original bearing trees

A sawed fir stump, 48 ins. diam., bears N. 32° E., 79 lks. dist., with healed blaze. (Record N. 30° E., 70 lks.)

A fir, 50 ins. diam., bears S. 41° W., 35 lks. dist., with healed blaze.

A sawed fir stump, 38 ins. diam., bears N. 49° W., 30 lks. dist., no marks visible on opened blaze.

and bearing trees mkd. by Irving

A cedar, 16 ins. diam., bears S. 82° E., 73 lks. dist., with healed blaze.