

County Surveyor's Record, Douglas County, Oregon

18056 Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
33.25	Plank Creek, 10 lks. wide, course N.; continue over river bottom.
34.155	True point for the closing cor. of secs. 3 and 4, hereinafter described. Continue over river bottom.
38.95	Smith River, 25 lks. wide, course S. 10° E.; continue over river bottom.
40.515	The cor. of secs. 33 and 34, perpetuated and recorded by N. E. Richardson, Deputy County Surveyor, in 1948, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 20 S R 6 W
S | S
33 | 34

1948

from which the remains of an original bearing tree

A sawed fir stump, 64 ins. diam., bears N. 71° E., 32 lks. dist., with scribe marks ¼ visible on opened blaze.

and a bearing tree mkd. by Richardson

A fir, 36 ins. diam., bears N. 24° W., 53 lks. dist., with healed blaze.

and a new bearing tree

A maple, 9 ins. diam., bears N. 19° E., 53 lks. dist., mkd. T20S R6W S34 BT.

The corner is located in a barbed wire fence line, extending E. and W.

Land, mountainous to flat.
Soil, sandy clay.
Timber, fir, cedar, hemlock, maple, yew, ash, alder, and willow; undergrowth, salal, Oregon grape, ferns hazel, blackberry, salmonberry, thimbleberry, huckleberry, vine maple, arrowwood, and young timber.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by William P. Wright, in 1884)

From the ¼ sec. cor. of secs. 2 and 3, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, and further perpetuated and recorded by Larry E. Monrean, Deputy County Surveyor, in 1975, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 21 S R 6 W
¼ S 3 | S 2

1961

FO. OK 12/92
L. Roberts
M116-43
C.S. 62/149