

County Surveyor's Record, Douglas County, Oregon

18057

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A sawed fir stump, 39 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ E.,
16 lks. dist., no marks visible. (Record,
S. 55° E.)

A sawed fir stump, 33 ins. diam., bears S. 67° W.,
14 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.

and the remains of a bearing tree mkd. by Godfrey

A sawed hemlock stump, 14 ins. diam., bears
N. $52\frac{1}{2}^{\circ}$ E., 37 lks. dist., with fragmentary
scribe marks visible on decayed blaze.

and a bearing tree mkd. by Monrean

A maple, 29 ins. diam., bears S. $3\frac{1}{2}^{\circ}$ E.,
263 lks. dist., with healed blaze.

and a new bearing tree

A fir, 4 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W.,
39 lks. dist., mkd. X BT.

N. $0^{\circ} 07'$ W., bet. secs. 2 and 3, marking and blazing
the true line.

Descend over NE. slope, through heavy timber and dense
undergrowth.

3.25 Ravine, drains E.; asc. over SE. slope.

19.50 Spur, slopes N. 60° E.; desc. over broken NW. slope,
changing to NE. slope.

44.22 The original closing cor. of secs. 2 and 3, perpetuated
and recorded by Milo E. Godfrey, Deputy County Surveyor,
in 1961, monumented with an iron post, $1\frac{1}{4}$ ins. diam.,
firmly set, projecting 8 ins. above ground, with brass
cap mkd.

COUNTY SURVEYORS OFFICE

T 20 S
S 35
S 3 | S 2
CC
T 21 S R 6 W
1961

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears
S. 60° E., 94 lks. dist., no marks visible.

A decayed fir stump, size indeterminate, bears
N. 59° W., 48 lks. dist., no marks visible.

and bearing trees mkd. by Godfrey

A fir, 16 ins. diam., bears S. 19° E., 167
lks. dist., with healed blaze.

A cedar, 48 ins. diam., bears S. 73° W., 230
lks. dist., with healed blaze.