

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 21 S., R. 6 W., Willamette Meridian, Oregon

18059

**CHAINS**

T 21 S R 6 W  

S 3	S 2
S 10	S 11

 1985

Fd. Ok by R. Ward  
 June 2002  
 M140-36

FD. OK 12/92  
 L. ROBERTS  
 M140-36  
 C.S. 6/3/97

from which

A fir, 9 ins. diam., bears N. 40° E., 21½  
 lks. dist., mkd. T21S R6W S2 BT.

A fir, 9 ins. diam., bears S. 85° E., 30½  
 lks. dist., mkd. T21S R6W S11 BT.

A hemlock, 14 ins. diam., bears S. 56½° W., 4  
 lks. dist., mkd. T21S R6W S10 BT.

A fir, 13 ins. diam., bears N. 52° W., 23  
 lks. dist., mkd. T21S R6W S3 BT.

Deposit a white "DEEP-1" magnetic marker at  
 base of stainless steel post.

S. 89° 08' W., bet. secs. 3 and 10.

Ascend over SE. slope, through heavy timber and dense  
 undergrowth.

0.60 Spur, slopes S. 10° E.; desc. over SW. slope.

2.25 Creek, 3 lks. wide, course S. 40° E.; asc. over SE.  
 slope.

21.20 Ridge, bears N. 10° E. and S. 10° W.; desc. over broken  
 NW slope, changing to SW. slope.

37.30 Creek, 2 lks wide, course N. 70° W.; asc. over NE.  
 slope.

39.425 Point for the 1/4 sec. cor. of secs. 3 and 10, at propor-  
 tionate distance; there is no remaining evidence of the  
 original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
 24 ins. in the ground, with brass cap mkd.

T 21 S R 6 W  

¼	S 3	S 10
---	-----	------

 1985

from which

A fir, 10 ins. diam., bears S. 68 ¾° W., 23  
 lks. dist., mkd. 1/4 S10 BT.

A fir, 10 ins. diam., bears N. 61° W., 6  
 lks. dist., mkd. 1/4 S3 BT.

Deposit a white "DEEP-1" magnetic marker at  
 base of stainless steel post.

Ascend over NE. slope.

40.20 Spur, slopes N.; desc. over NW. slope.