

# County Surveyor's Record, Douglas County, Oregon

18060

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**

44.65

Plank Creek, 2 lks. wide, course N.; asc. over broken NE. slope.

77.55

Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.

78.85

The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1961, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 14 ins. above ground, with washer mkd.

WILFORD N HAINES  
239  
SURVEY POINT  
DRAIN OR

from which the remains of an original bearing tree

A fir snag, 50 ins. diam., bears N. 10° E., 51 lks. dist., with fragmentary scribe marks visible on opened blaze.

and bearing trees mkd. by Haines

A fir, 38 ins. diam., bears S. 39° W., 68 lks. dist., with healed blaze and scribe marks 363 visible on bark blaze.

A fir, 30 ins. diam., bears N. 3° W., 89 lks. dist., with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.

*FD OK  
10/94  
M/21-24 A/B*

T 21 S R 6 W	
S 4	S 3
S 9	S 10
1985	

and new bearing trees

A fir, 6 ins. diam., bears N. 9½° E., 43 lks. dist., mkd. T21S R6W S3 BT.

A fir, 16 ins. diam., bears S. 23° E., 42 lks. dist., mkd. T21S R6W S10 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, United States Geological Survey triangulation station "SOUTH FORK," bears S. 27° 40' E., 83.16 chs. dist., monumented with a standard brass tablet, 3½ ins. diam., cemented in a boulder, flush with ground, with top mkd. SOUTH FORK 1940.

Land, mountainous.  
Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, madrone, willow, yew, alder, and chinquapin; undergrowth, salal, arrow-wood, hazel, ferns, Oregon grape, blackberry, and young timber.