

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional **18061**  
 Lines, T.21 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**

From the 1/4 sec.cor. of secs. 3 and 4, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1958, monumented with "T" shaped iron rod, 1 in. diam., firmly set, projecting 10 ins. above ground, with washer mkd.

WILFORD N HAINES  
 239  
 SURVEY POINT  
 DRAIN OR

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears S. 78° E., 10 lks. dist., no marks visible.

A sawed fir stump, 26 ins. diam., bears S. 80° W., 5 lks. dist., with fragmentary scribe marks visible on opened blaze.

and the remains of the bearing trees mkd by Haines

A fir snag, 51 ins. diam., bears N. 49° E., 275 lks. dist., with healed blaze.

A fir snag, 53 ins. diam., bears S. 55° E., 74 lks. dist., with scribe marks 1/4 S3 BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 21 S R 6 W  
           ½  
 S 4 | S 3  
 1984

*FD OK  
 10/19/84  
 M/21-24 A, B*

and new bearing trees

A fir, 4 ins. diam., bears N. 52° E., 7½ lks. dist., mkd. X BT.

A fir, 10 ins. diam., bears N. 0½° W., 14 lks. dist., mkd. ¼ S4 BT.

N. 0° 34' W., bet. secs. 3 and 4.

Descend over NW. slope, through heavy timber and dense undergrowth.

- 17.50 Ravine, drains N. 25° E.; asc. over SE. slope.
  - 23.40 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
  - 28.80 Spur, slopes N. 60° E.; desc. over NW. slope.
  - 37.95 Gravelled road, 15 lks. wide, bears N. 80° W. and S. 80° E.
  - 46.18 Intersect the S. bdy. of T. 20 S., R. 6 W.
- True point for the closing cor, of secs. 3 and 4.