

County Surveyor's Record, Douglas County, Oregon

18066 Dependent Resurvey of a Portion of the North Boundary
(Fifth Standard parallel South)
T. 23 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 35 and 36, determined from the original bearing trees:

A fir, 15 ins. diam., bears N. 15° E., 25 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears N. 18° W., 19 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FOOK 2/94
BY HOFFING
C.S. 63/15A*

T 22 S R 7 W
S 35/S 36
S 1
T 23 S R 7 W
1984

*FOOK 2/95
K Hoffing
CS 63/161-27*

N. 86° 34' W. on the N. bdy. of sec 1, marking and blazing the true line.

Ascend over broken NE. slope, through heavy timber and dense undergrowth.

5.97

The standard cor. of secs. 1 and 2, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, monumented with a 1 in. "T" shaped iron rod, loosely set, projecting 12 ins. above ground, from which the remains of bearing tree mkd. by Byars:

A root hole, bears S. 68° W., 22 lks. dist., with a down fir alongside, 26 ins. diam., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.

S 2/S 1
S C
T 23 S R 7 W
1984

from which new bearing trees

A fir, 8 ins. diam., bears S. 7° E., 33 lks. dist., mkd. T23S R7W S1 SC BT.

A hemlock, 13 ins. diam., bears S. 8 1/2° W., 79 lks. dist., mkd. T23S R7W S2 SC BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, oak, madrone, cedar, yew, maple, chinquapin, and alder; undergrowth, Oregon grape, salal, hazel, arrowwood, vine maple, blackberry, huckleberry, ferns, poison oak, and young timber.

S. 88° 47' W., on the N. bdy. of sec. 2.