

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the North Boundary 18067
 (Fifth Standard Parallel South),
 T. 23 S., R. 7 W. Willamette Meridian, Oregon

| CHAINS | |
|--------|--|
| 3.40 | Ascend over broken NE. slope, through heavy timber and dense undergrowth. Ridge, bears N. 25° W. and S. 25° E.; desc. broken SW. slope. |
| 13.87 | Point for the E 1/16 sec. cor. of sec. 35 only, hereinafter described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 22 S., R. 7 W. Descend over broken SW. slope. |
| 34.05 | The standard 1/4 sec. cor. of sec. 2, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 10 ins. above ground, with a washer, 1 in. diam., mkd. <div style="text-align: center;"> WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON </div> from which the remains of the original bearing trees <div style="margin-left: 40px;"> A decayed fir stump, size indeterminate, bears S. 40° E., 57 lks. dist., no marks visible. (Record, S. 45° E.) A sawed fir stump, 10 ins. diam., bears S. 70° W., 31 lks. dist., no marks visible. (Record, S. 67° W.) </div> and the remains of bearing tree mkd. by Haines <div style="margin-left: 40px;"> A cedar snag, 10 ins. diam., bears N. 6° W., 17 1/2 lks. dist., with scribe marks 1/4 S BT visible on open blaze. </div> At the corner point Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins, in the ground, directly over iron rod, with aluminum. cap mkd. <div style="text-align: center;"> $\frac{1}{4} S 2$ S C 1984 </div> from which new bearing trees <div style="margin-left: 40px;"> A fir, 4 ins. diam., bears S. 57 3/4° E., 37 lks. dist., mkd. X BT. A cedar, 19 ins. diam., bears S. 40 1/2° W., 19 lks. </div> <hr style="width: 20%; margin-left: 40px;"/> <div style="margin-left: 40px;"> S. 88° 50' W., beginning new measurement. </div> Descend over broken SW. slope. |