

County Surveyor's Record, Douglas County, Oregon

18068 Dependent Resurvey of a Portion of the North Boundary
(Fifth Standard Parallel South),
T. 23 S., R. 7 W., Willamette Meridian, Oregon

CHAINS
6.34

The 1/4 sec. cor. of sec. 35 only, T. 22 S., R. 7 W., reestablished and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 10 ins. above ground, with a washer, 1 in. diam., mkd.

WILFORD N HAINES
239
SURVEY POINT
DRAIN OREGON

from which the remains of bearing trees mkd. by Haines

A fir, 38 ins. diam., bears N. 13° E., 35 lks. dist., with scribe marks 1/4 S35 BT visible on bark blaze.

A fir snag, 23 ins. diam., bears N. 18° W., 24 lks. dist., with scribe marks 1/4 S35 BT visible on bark blaze.

At the corner point

Set an aluminum post, 28, ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with aluminum cap mkd.

T 22 S R 7 W
1/4 S 35
T 23 S R 7 W
1984

from which a new bearing tree

A grand fir, 27 ins. diam., bears N. 77° W., 58 dist., mkd. 1/4 S35 BT.

S. 89° 48' W., beginning new measurement.

Descend over SW. slope.

4.60

Spur, slopes S. 55° W.; desc. over broken NW. slope.

19.82

The W 1/16 sec. cor. of sec. 35 only, T. 22 S., R. 7 W., established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above ground, with a washer, 1 in. diam., mkd.

WILFORD N HAINES
239
SURVEY POINT
DRAIN OREGON

from which bearing trees mkd. by Haines

A cedar, 28 ins. diam., bears N. 54° E., 94 lks. dist., with scribe marks 1/16 S35 BT visible on open blaze.

A cedar, 22 ins. diam., bears N. 54° W., 75 lks. dist., with fragmentary scribe marks visible on partially healed blaze.