

# County Surveyor's Record, Douglas County, Oregon

18070 Dependent Resurvey of a Portion of the North Boundary  
(Fifth Standard Parallel South).  
T. 23 S., R. 7 W., Wilamette Meridian, Oregon

CHAINS	
	N. 89° 39' W., on the N. bdy. of sec. 3.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
6.67	The closing cor. of secs. 34 and 35, hereinafter described in the field notes of the dependent resurvey of the subdivisional lines, T. 22 S., R 7 W.
	Ascend over SE slope.
10.15	Spur, slopes S.; desc. over broken NW. slope, also gravelled road, 20 lks. wide, bears N. and S.
37.70	Creek, 10 lks. wide, course S. 60° W.; asc. over SE. slope.
39.65	The standard 1/4 sec. cor. of sec. 3, reestablished by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1960, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 3 ins. above ground with a washer, 1 in. diam., mkd.
	WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON
	from which a bearing tree mkd. by Haines
	A cedar, 31 ins. diam., bears S. 29° W., 37 lks. dist., with healed blaze. (Record, 40 lks.)
	At the corner point
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with aluminum cap mkd.
	$\frac{1}{4}$ S 3 S C T 23 S R 7 W 1984
	from which a new bearing tree
	A fir, 11 ins. diam., bears S. 73 1/2° E., 18 1/2 lks. dist., mkd. 1/4 S3 SC BT.
	N. 89° 36' W., beginning new measurement.
	Ascend over broken SE. slope
6.95	Spur. slopes S. 10° E.; desc. over broken SW. slope
28.35	Creek, 10 lks. wide, course S. 20° W.; asc. over SE. slope.
39.59	The standard cor. of secs. 3 and 4, perpetuated and recorded by John H. Markham Jr., Registered Engineer, No. 2880, in 1951, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of an original bearing tree: