

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the North Boundary **18071**  
 (Fifth Standard Parallel South),  
 T. 23 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 38 ins. diam., bears S. 28° W., 27 lks. dist., with fragmentary reverse scribe marks visible on open blaze, scribe marks S4 BT by Markam, visible on bark blaze.</p> <p>and bearing trees mkd. by Markam</p> <p>A fir, 27 ins. diam., bears S. 29 1/2° E., 80 lks. dist., with healed blaze.</p> <p>A madrone, 29 ins. diam., bears S. 47 1/2° W., 97 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\frac{S\ 4/S\ 3}{S\ C}</math> <p>T 23 S R 7 W 1984</p> </div> <p>Deposit iron pipe alongside iron post.</p> <p>Land, mountainous.                      Soil, rocky clay.                      Timber, fir, cedar, madrone, hemlock, oak, maple, ash, cherry, yew, dogwood, willow, alder, and chinquapin; undergrowth, arrowwood, hazel, Oregon grape, salal, huckleberry, salmonberry, poison oak, blackberry, ferns, pine maple, thimbleberry, and young timber</p>
	<p>Dependent Resurvey of a Portion of                      the Subdivisional Lines,                      T. 22 S., R. 7 W., Willamette Meridian, Oregon</p>
	<p>(Restoring the survey by William H. Byars, in 1871, the survey and resurvey by Winfield S. Chapman and Carl S. Nicklin, in 1897, and the resurvey by John M. Jelley and Donald R. Beck, in 1967)</p>
	<p>From the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp.</p> <p>N. 0° 06' E., bet. secs. 35 and 36, marking and blazing the true line.</p> <p>Descend over NE. slope, through heavy timber and dense undergrowth.</p>
8.15	<p>Creek, 1 lk. wide, course NE.; asc. over broken SE. slope.</p>
18.65	<p>Spur, slopes N. 40° E.; desc. over NW. slope.</p>
19.46	<p>The S 1/16 sec. cor. of secs. 35 and 36, established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 12 ins. above ground, with a washer, 1 in. diam., mkd.</p>