

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **18073**
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A hemlock, 19 ins. diam., bears N. 59° W., 15 lks. dist., mkd. 1/4 S35 Bt.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, yew, alder, chinquapin, oak, ash, madrone, maple, cherry, willow, and cascara; undergrowth, Oregon grape, salal, hazel, arrowwood, vine maple, blackberry, salmonberry, huckleberry, poison oak, ferns, manzanita, and young timber.</p>
	<p>From the 1/4 sec. cor. of secs. 34 and 35, reestablished and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above ground, with a washer, 1 in. diam., mkd.</p> <p style="text-align: center;">WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON</p> <p>from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 83° E., 12 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A yew, 15 ins. diam., bears S. 15°W., 25 lks. dist., with scribe marks / 35 B visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W <i>FO. OK 10/95</i> 1/4 <i>BY HOFFINE M119-78</i> S 34/S 35 1984</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 16° E., 15 lks. dist., mkd. 1/4 S35 BT.</p> <p>S. 0° 08' E., bet. secs. 34 and 35.</p> <p>Ascend over NW. slope, through heavy timber and dense undergrowth.</p>
3.65	Spur, slopes N. 60° W.; desc. over SW. slope, also dirt road, 15 lks. wide, bears N. 50° W. and S. 60° E.
23.90	Creek, 3 lks. wide, course S. 70° W.; asc. over NW. slope, also edge of gravelled road, 20 lks. wide, bears N. 30° W. and S. 20° W.
28.75	Gravelled road, 20 lks. wide, bears N. 50° W. and S. 80° E.
32.20	Gravelled road, 20 lks. wide, bears N. 50° W. and S. 70° E.
34.45	Spur, slopes S. 40° W.; desc. over SE. slope.