

# County Surveyor's Record, Douglas County, Oregon

18074 Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

4091

The closing cor. of secs. 34 and 35, on the S. bdy. of the Tp. (Fifth Standard Parallel South), reestablished and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 4 ins. above ground, with a washer, 1 in. diam., mkd.

WILFORD N HAINES  
239  
SURVEY POINT  
DRAIN OREGON

from which the remains of bearing trees mkd. by Haines

A fir snag, 18 ins. diam., bears N. 64° E., 43 lks. dist., with scribe marks T22S R7W S35 BT visible on open blaze.

A fir snag, 17 ins. diam., bears N. 18° W., 57 lks. dist., with scribe marks T22S R7W S34 BT visible on open blaze.

At the corner point

Set an iron post. 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.

T 22 S R 7 W  
C/C  
S 34/S 35  
S 3  
1984

from which new bearing trees

A fir, 10 ins. diam., bears N. 12 1/2° E., 12 1/2 lks. dist., mkd. T 22S R7W S35 CC BT.

A grand fir, 18 ins. diam., bears N. 15 1/2° W., 41 lks. dist., mkd. T22S R7W S34 CC BT.

From this point, the standard cor. of secs. 2 and 3, T. 23 S., R. 7 W., bears S. 89° 39' E., 6.67 chs. dist. hereinbefore described.

Point for the E 1/16 sec. cor. of sec. 35 only, is at proportionate position bet. the closing cor. of secs. 34 and 35, and the cor. of secs. 35 and 36, on the N. bdy. of sec. 2, T. 23 S., R. 7 W.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 35  
1984

from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 40° E., 30 lks. dist., with brass cap mkd. RM E 1/16 S35 30 LKS.1984, and an arrow pointing to the corner